
APPENDIX 2A PRELIMINARY GCLL DESIGN DETAILS

Acronyms

GCLL - Geosynthetic Clay Laminated Liner

CPE - Corrugated Polyethylene

UV - Ultra-violet



 VERTICAL DISTANCE BETWEEN ANCHOR TRENCHES TO VARY BETWEEN 40 AND 60 VERTICAL FEET DEPENDING ON ROLL LENGTH, RUNOUT LENGTH, AND ANCHOR TRENCH SIZING. VERTICAL DISTANCES WILL BE EVALUATED DURING FINAL DESIGN.


SPACING AND SIZING OF LATERAL DRAINAGE COMPONENTS WILL BE DETERMINED DURING FINAL DESIGN.

OVERALL COVER LAYOUT CONCEPTUAL COVER DESIGN SIMPLOT - SMOKY CANYON MINE

Geosyntec ^c consultants

DATE: AUGUST 2013 PROJECT NO. SC0564

FIGURE






CONCEPTUAL COVER DESIGN
SIMPLOT - SMOKY CANYON MINE

Ceosyntec DATE: AUGUST 2013

PROJECT NO. SC0564

CONCEPTUAL COVER DESIGN
SIMPLOT - SMOKY CANYON MINE

FIGURE
2




TOE DRAIN CONCEPTUAL COVER DESIGN SIMPLOT - SMOKY CANYON MINE

Geosyntec consultants

DATE: AUGUST 2013
PROJECT NO. SC0564

3

FIGURE



PHASED CAP CONSTRUCTION CONCEPTUAL COVER DESIGN SIMPLOT - SMOKY CANYON MINE

Geosyntec consultants

DATE: AUGUST 2013
PROJECT NO. SC0564

FIGURE 5